

GLASSTILE RECOMMENDED APPLICATIONS

LOCATION	WALLS		SHOWERS		STEAM SHOWERS ¹		COUNTERTOPS		SUBMERGED		FLOORS		FLOOR USAGE LEVEL			
	Interior	Exterior	Walls	Floors	Walls	Floors	Powder Room	Kitchen	Water Features	Pools & Spas	Interior	Exterior	Light Residential	Residential	Heavy Residential	Light Commercial
DEVOTION³																
Mosaic (Mounted)	•	•	•		•											
Field Tile (Unmounted)	•		•		•											
BLUE²																
All	•	•	•	•	•	•	•	•	•	•	•	•	•			
MUSE																
Irid	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Non-Irid	•	•	•		•		•		•	•						
Matte	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Twilight	•	•	•		•		•	•								•
HARMONIA¹ + AVANI¹																
Irid	•	•	•	•			•					•		•	•	•
Non-Irid	•	•	•				•									
Matte	•	•	•	•			•					•		•	•	•
Muse Twilight	•	•	•				•									
TESSERA + FACETS																
Irid	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Non-Irid	•	•	•		•		•		•	•						
Matte	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
GEOLOGIE¹																
Irid	•	•	•				•					•		•	•	•
Non-Irid	•	•	•				•									
Matte	•	•	•				•					•		•	•	•
CASA CALIFORNIA²																
Irid	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Non-Irid	•	•	•		•		•		•	•						
Matte	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
ELEVATIONS²																
Irid	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Non-Irid	•	•	•		•		•		•	•						
Matte	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
KINSHIP																
All	•	•	•		•											

¹ Not recommended for exterior use in freeze-thaw climates. **NOTE:** Irid = Iridescent, Non-Irid = Non-Iridescent
² Tiles with any edge longer than 5" or trim tile with any edge longer than 2.5" are not recommended for shower floors or submerged applications, e.g. pools, spas and water features.
³ The following Devotion colors are **NOT** recommended for exterior applications: Gold, Silver Leaf, Water Mirror, Smoke Mirror, Lustre, Gilt, Heirloom, Nocturne, Astral and Helios. The following Devotion colors are **NOT** recommended for showers or steam showers: Gold, Silver Leaf, Water Mirror, Smoke Mirror.
⁴ In general, Oceanside Glasstile only recommends opaque tile in steam showers. However, in some instances, translucent tile may be used when installed with specific installation materials. For additional information, contact Oceanside Glasstile Technical Services at techsupport@glasstile.com or 877-648-8222.

FIREPLACES: All Oceanside Glasstile products are recommended for use on fireplace surrounds (wall tile) and/or hearth (floor tile) applications. Oceanside Glasstile products are **NOT** recommended for use inside fireboxes.

SALT WATER POOLS: All Oceanside Glasstile products recommended for use in pools (see chart above) are not adversely affected by exposure to salt water and are recommended for use in both fresh water and salt water pools.

SEALING NATURAL STONE: Avani, Harmonia, Geologie and Kinship all include natural stone components. To protect the natural stone, seal installations with either Oceancare High Performance Penetrating Sealer (natural look) or Oceancare High Performance Enhancing Sealer (color enriching) and maintain with an appropriate Oceancare cleaning product. For additional information, contact Oceancare Technical Services at techsupport@glasstile.com, 877-648-8222 or visit oceancareproducts.com.

LIGHT RESIDENTIAL: Residential flooring areas subject to soft-soled footwear or normal footwear traffic without heavy dirt. Some examples would be: interior rooms such as bathrooms and bedrooms without exterior access.
RESIDENTIAL: Residential flooring areas that are subject to soft-soled footwear or normal footwear traffic with small amounts of abrasive soil. Some examples would be: living or dining rooms.
HEAVY RESIDENTIAL: Residential flooring areas that are subject to normal footwear traffic with occasional amounts of abrasive soil. Some examples would be: halls, kitchens and corridors.
LIGHT COMMERCIAL: Non-industrial, commercial flooring areas that are subject to normal footwear traffic (less than 50 people per hour) with occasional amounts of abrasive soil. Some examples would be: boutique showrooms and corporate office spaces.

TEST RESULTS									
TEST NUMBER	C1028		C648	ISO 10545-4		C424	C650	C373	C1026
Test Name	Static Coefficient of Friction		Breaking Strength*	Breaking Strength	Modulus of Rupture	Crazing Resistance	Chemical Resistance	Water Absorbtion	Freeze-Thaw Resistance
	Dry	Wet							
BLUE									
ALL	N/A	N/A	≥ 350 lbf	N/A	N/A	No Effect 1 Cycle @150 PSI	No Effect	< .5%, Impervious	Pass
MUSE									
Iridescent	.77	.55	≥ 350 lbf	N/A	N/A	No Effect 1 Cycle @150 PSI	No Effect	< .5%, Impervious	Pass
Non-Irid	.84	.45							
Matte	.86	.81							
Twilight	.78	.49							
HARMONIA									
Iridescent	.77	.55	≥ 350 lbf	N/A	N/A	N/A	N/A	N/A	N/A
Non-Irid	.84	.45							
Matte	.86	.81							
Twilight	.78	.49							
TESSERA + FACETS									
Iridescent	.76	.60	≥ 350 lbf	N/A	N/A	No Effect 1 Cycle @150 PSI	No Effect	< .5%, Impervious	Pass
Non-Irid	.76	.30							
Matte	.77	.65							
GEOLOGIE									
Iridescent	.80	.60	≥ 350 lbf	N/A	N/A	N/A	N/A	N/A	N/A
Non-Irid	.79	.59							
Matte	.77	.65							
CASA CALIFORNIA + ELEVATIONS									
Iridescent	.76	.48	N/A	≥ 1500 N	≥ 35 N/mm ²	No Effect 1 Cycle @150 PSI	No Effect	< .5%, Impervious	Pass
Non-Irid	.81	.36							
Matte	.77	.65							

* Test is only performed on glass tile and does not include test results for glass tile with any one side which is less than 1".